

CMA ACOUSTICAL SYSTEMS

SYSTEM	STANDARD THICKNESS	STANDARD DENSITY	STANDARD WIDTHS	MAX WIDTHS	STANDARD LENGTH	MAXIMUM LENGTH	STANDARD FACINGS	ACOUSTICAL RANGE
Quiet Coordinates	2"	Dual 1.8 & 3#	48, 60"	60"	4, 5, 8, 10'	10'	Matte	.90–1.00
Encapsulated Pads & Rolls	1/2 – 6"	3/4 – 7#	12, 18, 24, 36, 48"	72"	2, 4'	10' – PVC 30' – Poly	Poly PVC, PVF	.65 – 1.15
Baffle Systems	1, 1-1/2, 2"	1-1/2 – 7#	18, 24, 36, 48"	48"	2, 4'	10'	PVC, PVF Matte, Sailcloth	.90 – 1.15
Wall Panel Systems	1 - 2"	2-1/2, 3, 4, 6#	24, 48"	48"	4, 8'	10'	PVC, PVF Sailcloth, Glass	.65 – 1.15
Banner Systems	1 - 4"	1, 1-1/2, 2#	48"	48"	8'	30'	Sailcloth Perf, PVC	.85 – 1.15
Ceiling Panels	1 - 2"	3.0#	20, 24, 48, 60"	60"	4, 5, 8, 10'	10'	Glass Cloth 5 Patterns	.85 – 1.00
Hygienic Ceilings & Walls	1, 1-1/2, 2"	4#	24"	48"	2, 4'	5'	White Teldar PVF	.85 – 1.00

NOTES: 1. Other facings, densities, and thickness may be available as a custom product. 2. Acoustical performance will vary with thickness and type of facing, density, and thickness of fiberglass base. 3. Maximum length will vary according to facing selected. 4. Other acoustical properties such as CAC (STC) are available: Call CMA, Inc. to discuss.